

745XA

PAINT STRIPPER

A thickened paint remover, designed for use in the Aviation, Naval, Automotive and general engineering industries.

PROPERTIES

APPEARANCE: Viscous, yellow liquid
ODOUR: Phenolic
pH (100 %): 9,0 - 9,6
S.G.: 1,15 - 1,17

FEATURES

1. Complies with all requirements of Boeing Spec.D6-17487
2. Effectively removes Epoxy, Polyurethane and other organic coatings.
3. Complete rinsing.
4. Versatile in application requirements.
5. Contains waxes, which slows down solvent evaporation.
6. Approved by Boeing, SAAF.

DIRECTIONS FOR USE

1. Use as received.
2. Mask ALL AREAS constructed of plastic, plexiglass or rubber.
3. Apply by means of brush, Barrel pump, or similar nonatomizing spray equipment.
4. Allow sufficient contact time to thoroughly loosen paint.
5. Once blistering is visible on total area, rinse with high pressure, high volume cold water, or with a steam cleaning machine.
6. Some coatings may require agitation with a brush to loosen all paint residues.

SAFETY PRECAUTIONS AND FIRST AID

PRODUCT CONTAINS CHLORINATED HYDROCARBON AND PHENOLS

EYES: Use face shields when handling product. Serious damage to eyes when in contact. Flush for at least 15 minutes with water. Seek medical attention immediately.

SKIN: Serious skin burns due to phenol. Wash affected parts immediately with ALCOHOL (ethanol, methanol or propyl alcohol). Thereafter, wash well with soap and water. Seek medical attention.

NOTE: AS A RESPONSIBLE SAFETY PRECAUTION, IT IS ADVISED THAT AT LEAST 25 L OF ALCOHOL IS KEPT ON HAND WHEN USING PHENOLIC PAINTSTRIPPERS.

INGESTION: DO NOT INDUCE vomiting. Give person eggwhite and milk to drink. Seek medical attention immediately.

INHALATION: Avoid inhaling vapours. Remove person to fresh air. If difficulty is experienced with breathing, administer oxygen. Seek medical attention immediately.

NOTE: DO NOT MIX WITH ANY CHEMICALS, unless indicated by the manufacturer

REF: D745XA

DATE: 05.03.2018